

PRODUCT NAME: PUTTING GRASS

APPLICATION: GOLF

MATERIAL

PILE: PE fibrillated tape (texturized)
 PRIMARY BACKING: 100% PP
 SECONDARY BACKING: SBR Latex
 GAUGE: 3/16"
 COLOR: olive green

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	9.500	± 10%
Pile width	[mm]	12	± 5%
Pile thickness	[µm]	80	± 10%
Pile weight per unit area	[g/m ²]	1.568	± 10%
Stitch rate per 10 cm (length)	[-/10 cm]	20	± 10%
Number of tufts/m ²	[-/m ²]	41.995	± 10%
Number of piles/m ²	[-/m ²]	83.990	± 5%
Pile height	[mm]	16	± 5%
Weight primary backing	[g/m ²]	170	± 10%
Weight secondary backing	[g/m ²]	950	± 10%
Total weight	[g/m ²]	2.688	± 10%
Turf withdrawal force	[N]	> 15	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,01	± 0,02

COMMENTS:

Recommended infill: quartz sand 0,3 – 0,8 mm -> ± 14 kg/m²

Any supplementary information and certificates are available upon request at our sales department. According to the Regulation (EC) No 1907/2006 (REACH), this product does not contain any dangerous substances.

JUTA a.s. reserves the right to amend the technical specifications of the above mentioned product. The delivered product may slightly differ from these data. JUTA a.s. guarantees the technical quality of the product.

manufactured by

