

TECHNICAL SHEET

valid from 1.2.2010

review 1.1.2011

PRODUCT NAME:	SCÉNIC
APPLICATION:	LANDSCAPING
MATERIAL:	PILE: PE monofilament – mild lens profil (straight + texturized)
	PRIM. BACKING: 100% PP
	SECONDARY BACKING: SBR Latex
GAUGE:	3/8"
COLOR:	bicolor green, sand

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	14.200/16	± 5%
Pile width	[mm]	0,9	± 10%
Pile thickness	[µm]	170	± 10%
Pile weight per unit area	[g/m ²]	2.144	± 10%
Stitch rate per 10 cm (length)	[-/ 10 cm]	18	± 1
Number of tufts / m ²	[-/m ²]	18.898	± 5%
Number of piles / m ²	[-/m ²]	604.736	± 5%
Pile height	[mm]	35	± 10%
Weight primary backing	[g/m ²]	172	± 10%
Weight secondary backing	[g/m ²]	700	± 10%
Total weight	[g/m ²]	3.016	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,00; 2,00	± 0,02

COMMENTS:

Recommended infill: non filled

Any supplementary information and certificates are available upon request at our sales department.
According to the Directive 76/ 769 this product does not contain any dangerous substances.



Juta a.s., Dukelská 417
544 15 Dvůr Králové nad Labem,
Česká republika
e-mail: jutagrass@juta.cz
Fax +420 499 314 572

www.juta.cz

JUTAgrass Česká republika
Na Borkách 89
Dvůr Králové nad Labem
Telefon: +420 499 314 567
+420 499 314 575